FISCHBEIN

Model 400T NS™

Tape Sewing System

Fast
Cost-effective
Aesthetic closure

The Model 400T NS is recognized as the leading tape sewing system in today's bagclosing industry. Fast and cost-effective, this dependable bag-sewing system will operate in the most demanding industrial environments.

Specifically designed for multi-wall paper and laminated woven polypropylene bags, the Model 400T NS is capable of operating at bagging speeds up to 55 linear feet per minute.

The Model 400T NS features the Empress® Series 101 Sewing Head with its proven self-lubricating design. A full range of available options enables the 400T NS to operate in semi- or fully automated bagging lines. Its unique, compact pedestal makes moving the 400T NS fast and easy while the corrosion-resistant finish makes it suitable for almost any location.

If bag-top trim and tape clippings are a concern, you can partner your 400T NS with our cost-effective TRS-100 or 200 Trim Removal systems.

The 400T NS is available only from Fischbein, your source for complete bag-closing solutions.



FISCHBEIN® COMPANY



Swing feature

The exclusive sewinghead swing feature makes threading the 400T NS a snap, and provides full access for cleaning and easy head removal.



Tape and thread cutter

Activated by a PLC-controlled photoelectric eye, this pneumatic system automatically cuts the crepe tape and thread at the completion of the sewing cycle.



Tape folder

Automatically guides and positions the crepe tape at the top of the bag mouth to ensure a securely sewn bag closure.



Infeed system

Fast. Safe. Automated. The leading edge of the bag is fed into the infeed, which automatically trims the bag top and guides the bag through the entire sewing process.



Emergency stop

Operator can immediately stop the entire sewing system.

Model 400T NS™

Tape Sewing System

Equipment Specifications

Sewing head

Fischbein Empress® 101 for tape sewing

Dimensions

| Height | 105 inches (266.7 cm) fully extended |
|-----------------|--------------------------------------|
| Width | 46 inches (116.8 cm) |
| Depth | 41 inches (104.1 cm) |
| Shipping weight | 750 pounds (341 kg) |

Pedestal height

Manually adjustable with total travel of 26 inches (66cm)

Electrical

| Power Supply230 volts, 1ph, 60 Hz | |
|---|--|
| 230 volts, 3ph, 60 Hz | |
| 380 volts, 3ph, 50 Hz | |
| 460 volts, 3ph, 60 Hz | |
| 575 volts, 3ph, 60 Hz | |
| Maximum current20 amps | |
| Complies with NEC wiring codes, standard NEMA 12 dust-tight | |

Pneumatic

Compressed air source: 90 psi, 1 cfm (dry air)
Air consumption (loaded with all options): 15 SCFM

Closing speed

Up to 55 linear fpm, calculated at 2.5 stitches per inch, depending on bag material

Bag size

| Width | 4-26 inches (10.2-66 cm) |
|-------------------|------------------------------|
| Height | 45 inches (114.3 cm) |
| Gussets | Any size including flat bags |
| Minimum free top | 6 inches (2.36 cm) |
| Filled bag weight | 1-110 pounds (0.45-50 kg) |

FISCHBEIN® COMPANY

Smart Solutions™ Bag weighing-handling-closing

151 Walker Road Statesville, N.C. 28625 704.871.1159 sales@fischbein.com